

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently amended): A pipe coupling for joining a first pipe to pipes of varying diameters, comprising,  
a first hollow fitting having opposite first and second ends,  
with the first end being adapted for connection to a first pipe,  
a second hollow fitting having first and second ends with the  
second end ~~being joined to fitting within~~ the second end of  
the first hollow fitting in sealed condition to define a  
fluid conduit extending through interiors of the first and  
second hollow fittings,  
first and second adjacent wells in the second hollow fitting,  
with the first well being adjacent the second end of the  
second fitting and having an upper end terminating in the  
first well, with both the first and second wells comprising  
at least a part of the fluid conduit,  
the first and second wells being cylindrical in shape with the  
second wall having a diameter greater than the diameter of  
the first well, whereupon inlet pipes having outside  
diameters complimentary in size to the diameters of the  
wells can be selectively and alternately secured within the  
respective wells to fluidly connect such pipes to the fluid  
conduit and the first hollow fitting.
2. (Original): The pipe coupling of claim 1 wherein the first  
and second wells have side walls adaptable for being fixedly  
secured to the inlet pipes.

3. (Original): The pipe coupling of claim 1 wherein the first hollow fitting is comprised of metal and the second hollow fitting is comprised of plastic.

4. (Currently amended): A pipe coupling for joining a first pipe to pipes of varying diameters, comprising,  
a first hollow fitting having opposite first and second ends,  
with the first end being adapted for connection to a first pipe,

a second hollow fitting having first and second ends with the  
second end ~~being joined to fitting within~~ the second end of  
the first hollow fitting in sealed condition to define a  
fluid conduit extending through interiors of the first and  
second hollow fittings,

first and second adjacent wells in the second hollow fitting,  
with the first well being adjacent the second end of the  
second fitting and having an upper end terminating in the  
first well, with both the first and second wells comprising  
at least a part of the fluid conduit,

the first and second wells being cylindrical in shape with the  
second wall having a diameter greater than the diameter of  
the first well, whereupon inlet pipes having outside  
diameters complimentary in size to the diameters of the  
wells can be selectively and alternately secured within the  
respective wells to fluidly connect such pipes to the fluid  
conduit and the first hollow fitting;

the first hollow fitting is comprised of metal and the second  
hollow fitting is comprised of plastic;

a plastic pipe having an end secured within one of the wells.

5. (Currently amended): A pipe coupling for joining a first pipe to pipes of varying diameters, comprising,  
a first hollow fitting having opposite first and second ends,  
with the first end being adapted for connection to a first pipe,  
a second hollow fitting having first and second ends with the  
second end ~~being joined to fitting within~~ the second end of  
the first hollow fitting in sealed condition to define a  
fluid conduit extending through interiors of the first and  
second hollow fittings,  
first and second adjacent wells in the second hollow fitting,  
with the first well being adjacent the second end of the  
second fitting and having an upper end terminating in the  
first well, with both the first and second wells comprising  
at least a part of the fluid conduit,  
the first and second wells being cylindrical in shape with the  
second wall having a diameter greater than the diameter of  
the first well, whereupon inlet pipes having outside  
diameters complimentary in size to the diameters of the  
wells can be selectively and alternately secured within the  
respective wells to fluidly connect such pipes to the fluid  
conduit and the first hollow fitting;  
a pressurized fluid supply pipe having an end secured within one  
of the wells.

6. (Original): The coupling of claim 1 wherein the first hollow fitting has means on its first end for coupling to a first pipe.